

## OLDOPAL-Viscosity Reducer

Viscosity Reducer for Highly Filled UP Systems

Prod. No. 742-0018

**Product description** OLDOPAL-Viscosity Reducer is a styrene-free solution of viscosity reducing polymers in methyl methacrylate.

**Applications** It is used to reduce viscosity of the highly filled Synolite 8175-W-1 and OLDOPAL S 453-TV systems.

Specifications / technical data	Property	Test method	Value	Unit
	Density at 20 °C	DIN 53 217/2	approx. 1.0	g/ml
	Viscosity at 20 °C in an ISO cup	EN ISO 2431	9 - 11	s
	Flash point	DIN 53 213	+ 10	°C

**Directions for use** Approx. 1-2 parts by weight OLDOPAL-Viscosity Reducer are added to 100 parts by weight resin.

**Note:** Filler stabilisation in resin is broken down by OLDOPAL-Viscosity Reducer. For this reason, batches should not be larger than can be used in one day!

**Storage/Handling** This product must be stored cool in closed containers, protected from sunlight. Shelf-life is at least 6 months in unopened, original containers stored up to a temperature of 20 °C.

Note: The Information given above is based on our current state of knowledge and experience. In view of the many factors that may influence working conditions and the application of our products, the user is not relieved from carrying out his own tests and experiments. No legally binding warranty of certain properties or suitability for a particular purpose can be derived from this information. It is the responsibility of the receiver or user of our products to observe proprietary rights as well as existing laws and regulations. The latest version of the corresponding EU Safety Data Sheet must also be observed.

BÜFA Gelcoat Plus GmbH & Co. KG  
Hohe Looge 2-8  
26180 Rastede

Germany

Phone +49 4402 975-0

Fax +49 4402 975-300

gelcoatplus@buefa.de  
www.gelcoatplus.de / www.buefa.de